











Electri Charge -A48

A48W132EN15 / A48W316EN15 / A48W332EN15



-  Anti-Pressure Inflaming
-  Over Current Protection
-  Over Voltage Protection
-  Under Voltage Protection
-  PEN Protection (Optional)
-  CP Protection
-  Water-proof Protection
-  Over Temperature Protection

• Charger parameter details

Version	CE version	FCC version
Input voltage	100-240VAC 50/60Hz 1Phase 400VAC 50/60Hz 3Phase	100-240VAC 50/60Hz 1Phase
Output voltage	100-240VAC 50/60Hz 1Phase 400VAC 50/60Hz 3Phase	100-240VAC 50/60Hz 1Phase
Max current	32A	32A
Max power	7KW / 11KW / 22KW	7KW
input frequency	50Hz / 60Hz	50Hz / 60Hz
Charging interface	IEC 62196 Type 2	SAE J1772 Type 1
Cable Length	5m / customizable	5m / customizable
Function		
Ethernet/WIFI/4G/Bluetooth	Bluetooth / WIFI+IC Card	Bluetooth / WIFI+IC Card
Screen		
Cuttent adjustable	Configurable limit of charging current via APP	Configurable limit of charging current via APP
Start time set up	by phone	by phone
Working Environment		
Safety	Overvoltage protection, undervoltage protection, overload protection, leakage protection, grounding protection, over-temperature protection, lightning protection	
RCD	RCD Type B protection	RCD Type B protection
IP Degree	IP55	IP55
Operating Temperature	-25°C~+50°C	-25°C~+50°C
Working Place	Indoor / Outdoor	Indoor / Outdoor
Guarantee		
Warranty	12 months	12 months
Certificate	CE	FCC
Packing		
Product Size	240*153*83 mm	240*153*83 mm
Net Weight	4-6kg	4-6kg