



Flexi Charge - A15

A63W116EN09 / A63W132EN09 / A63W316EN09 / A63W332EN09 / A63W140US09



- Anti-Pressure Inflaming
- Overcurrent Protection
- Overvoltage Protection
- Undervoltage Protection
- CP Protection
- Water-proof Protection
- Overtemperature Protection



• Charging operation process

1 Download the App and sign up an account.

2 Plug the charging cable into EV.

3 Scan QR code to start the charging

4 Stop charging in the App.

• Charger parameter details

Datasheet	Model	3.5Kw	7Kw	11Kw	22Kw	9.6Kw
Input	Power Supply	1P+N+PE	1P+N+PE	3P+N+PE	3P+N+PE	1P+N+PE
	Rated Voltage	230VAC	230VAC	400VAC	400VAC	230VAC
	Rated Current	16A	32A	16A	32A	40A
	Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Output	Output Voltage	230VAC	230VAC	400VAC	400VAC	230VAC
	Maximum Current	16A	32A	16A	32A	40A
User Interface	Charge Connector	Tpye 2	Tpye 2	Tpye 2	Tpye 2	Tpye 1
	Cable Length	5m	5m	5m	5m	5m
	Status indicator	LED Indicator / LCD (Optional)				
	Display screen	2.8 -inch LCD (Optional)				
	Adjustable power	The plug comes with temperature detection and maximum output power recognition. The current can be adjusted downwards.				
Communication	Start Mode	Plug&Play	Plug&Play	Plug&Play	Plug&Play	Plug&Play
	WiFi / Bluetooth	Optional	Optional	Optional	Optional	Optional
Safety	RCD	Type A+DC 6mA				CCID20
	Ingress Protection	IP66	IP66	IP66	IP66	IP66
	Impact Protection	IK10	IK10	IK10	IK10	IK10
	Electrical Protection	Over current protection, Residual current protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Overtemperature protection				
	Certification	CE	CE	CE	CE	FCC
	Warranty	18 months	18 months	18 months	18 months	18 months
Environment	Work Temperature	-30°C~+50°C	-30°C~+50°C	-30°C~+50°C	-30°C~+50°C	-30°C~+50°C
	Work Humidity	5%~95%	5%~95%	5%~95%	5%~95%	5%~95%
	Work Altitude	<2000m	<2000m	<2000m	<2000m	<2000m