



Energi Flow -A6

A6B132EN18 / A6B316EN18 / A6B332EN18



- Anti-Pressure Inflaming
- Overcurrent Protection
- Overvoltage Protection
- Undervoltage Protection
- Leakage Protection
- CP Protection
- Water-proof Protection
- Overtemperature Protection
- Equipped With Wifi



• Product Parameters

Datasheet	Model	7KW/11KW/22KW
Input	Power Supply	1P+N+PE/3P+N+PE
	Rated Voltage	220V/380V
	Rated Current	16A/32A
	Frequency	50/60 Hz
Output	Output Voltage	220V/380V AC
	Maximum Current	16A/32A
	Rated Power	7KW/11KW/22KW
User Interface	Charge Connector	Type 2 Cable
	Cable Length	5m
	Enclosure	METAL
	LED Display	4.3" black color LED touch screen
	Start Mode	Plug and play/ RFID/APP
Safety	Emergency Stop	Yes
	Ingress Protection	IP65
	Impact Protection	IK10
	Electrial Protection	Over current protection,Residual current protection,Ground protection, Surge protection,Over/Undervoltage protection,Over/Under frequencyprotection, Over/Under temperature protection
	Certification	CE
	Certification Standard	ENIEC 62196,61851
	Warranty	2 Years
Evironment	Installation	Wall-mount / Pole-mount
	Work Temperature	-20°C~+50°C
Package	Package Dimension	480*320*300mm
	Gross Weight	7.5KG
	External Package	Carton