



# VoltPlug -A2

A60W132EN18-DB / A60W316EN18-DB / A60W332EN18-DB



## Flexible Option

Type 1 or Type 2 charging cable

## Quality Cable

Our cables are made of TPU. That cable is comfortable to touch, better wear resistance and is able to withstand high temperatures.


## Secure and Safe

6mA DC residual current protection  
Anti-welding protection

## Long Working Life

The plug of the EV charging cable with a service life of more than 10000 times. Insertion force (non-locking state) <100N



 Anti-Pressure Inflaming

 PEN Protection (Optional)


 Over Current Protection

 CP Protection

 Over Voltage Protection

 Water-proof Protection

 Under Voltage Protection

 Over Temperature Protection

## • Charger parameter details

| Datasheet      | Model                  | Parameters  |
|----------------|------------------------|---|
| Input          | Power Supply           | 1P+N+PE/3P+N+PE   |
|                | Rated Voltage          | 220V/380V   |
|                | Rated Current          | 16A/32A   |
| Output         | Frequency              | 50+2Hz  |
|                | Output Voltage         | 220V/380V AC  |
|                | Maximum Current        | 16A*2/32A*2   |
| User interface | Rated Power            | 14kw(7kw*2)/22kw(11kw*2)/44kw(22kw*2)   |
|                | Charge Connector       | Type 2 Socket   |
|                | Cable Length           | 0m  |
|                | Enclosure              | METAL   |
|                | LED Display            | 7" LED touch screen   |
| Safety         | Start Mode             | Plug and play/ RFID/APP   |
|                | Emergency Stop         | Yes   |
|                | Ingress Protection     | IP65  |
|                | Impact Protection      | IK10  |
|                | Electrial Protection   | Over current protection, Residual current protection, Ground protection, Surge protection, Over/Undervoltage protection, Over/Under frequency protection, Over/Under temperature protection |
| Environment    | Certification          | CE  |
|                | Certification Standard | ENIEC 62196, 61851  |
|                | Warranty               | 1 Year  |
|                | Installation           | Floor-mount   |
| Package        | Work Temperature       | -30°C~+50°C   |
|                | Work Humidity          | 3%~95%  |
|                | Work Altitude          | <2000m  |
| Package        | Product Dimension      | 440*250*1550mm  |
|                | Package Dimension      | 480*290*1600mm  |
|                | Gross Weight           | 50KG  |
|                | External Package       | Wooden box  |