



# Electri Charge -A19

A19W132EN07 / A19W316EN07 / A19W332EN07



- Anti-Pressure Inflaming
- Overcurrent Protection
- Overvoltage Protection
- Undervoltage Protection
- PEN Fault Protection
- CP Protection
- Water-proof Protection
- Overtemperature Protection
- 4.3 Inches Colors LCD Screen
- Equipped With Wifi



## • Product Parameters

Input voltage	100-240VAC 50/60Hz 1Phase 400VAC 50/60Hz 3Phase	100-240VAC 50/60Hz 1Phase
Output voltage	100-240VAC 50/60Hz 1Phase 400VAC 50/60Hz 3Phase	100-240VAC 50/60Hz 1Phase
Max current	32A	32A/40A/48A
Max power	7KW / 11KW / 22KW	7KW/9.6KW/11.5KW
input frequency	50Hz / 60Hz	50Hz / 60Hz
Charging interface	IEC 62196 Type 2	SAE J1772 Type 1
Cable Length	5m / customizable	5m / customizable
<b>Function</b>		
Ethernet/WIFI/4G/Bluetooth	Opt 1: Basic / Opt 2: wifi+IC Card	Opt 1: Basic / Opt 2: wifi+IC Card
Screen	LCD	LCD
Protocol	OCPP 1.6j	Wi-Fi 802.11b/g/n@2.4GHz
Current adjustable	by phone	by phone
Start time set up	by phone	by phone
<b>Working Environment</b>		
Safety	7 safety protection	7 safety protection
RCD	Type A, AC 30mA	Type A, AC 30mA
IP Degree	IP55	IP55
Operating Temperature	-25°C~+50°C	-25°C~+50°C
Working Place	Indoor / Outdoor	Indoor / Outdoor
<b>Guarantee</b>		
Warranty	24 months	24 months
Certificate	CE/ ISO/ TUV	ISO/ FCC/ TUV/ UL
<b>Packing</b>		
Product Size	385*284*80mm	385*284*80mm
Net Weight	4-6 kg	4-6 kg

## • Plug Optional

Customized according to your needs

